

YHM -S Serie

Input:DC 24V± 10%

Model	Output Voltage (kVdc)	Output Current (mA)	Power (W)	Ripple (% p-p)	Dimensions(mm) W x L x H	Overroll Length L0	Installation P1x P2
YHM - S10* 03	0~ 10	0.3	3	0.01	100x 120x 38	140	70x 195
YHM - S10* 10		1.0	10	0.01			
YHM - S10* 15		1.5	15	0.01			
YHM - S10* 20		2.0	20	0.02			
YHM - S15* 03	0~ 15	0.2	3	0.01	100x 140x 38	160	70x 150
YHM - S15* 10		0.66	10	0.01			
YHM - S15* 15		1.0	15	0.01			
YHM - S15* 20		1.33	20	0.02			
YHM - S20* 03	0~ 20	0.15	3	0.01	100x 160x 38	180	70x 170
YHM - S20* 10		0.5	10	0.01			
YHM - S20* 15		0.75	15	0.01			
YHM - S20* 20		1.0	20	0.02			
YHM - S30* 03	0~ 30	0.1	3	0.01	100x 160x 38	180	70x 170
YHM - S30* 10		0.33	10	0.01			
YHM - S30* 15		0.5	15	0.01			
YHM - S30* 20		0.66	20	0.02			

- Exclusive use adapter is prepared in the case of use with commercial AC power input.
- The above table is a representative example. Please inquire about the necessary output specification.

<Mode >

